



API-Documentatie Arthurian Fiction

Service

The Arthurian Fiction narratives and manuscripts database is available as a web application and as a service with an API. The API is exposed to the world in JSON format (for a specification see <http://json.org/>). The service is available on <https://service.arthurianfiction.org>. For human users, the service has a limited html representation of the objects exposed. The service is used by the arthurianfiction.org site itself.

Objects

The service exposes four different objects:

- manuscripts available under <https://service.arthurianfiction.org/manuscripts>
- narratives available under <https://service.arthurianfiction.org/narratives>
- persons <https://service.arthurianfiction.org/persons>

Manuscripts, narratives and persons are separate objects; they may be linked by a relation. Relations contain links between two different objects: between a person and a manuscript or narrative or between a manuscript and a narrative. Relations are typed, the type indicates the nature of the relation (e.g. an *author* typed relation between a person and a manuscript).

Single objects may be retrieved by specifying the id of the object. For example the manuscript MAN0000000015 is retrieved by url <https://service.arthurianfiction.org/manuscript/MAN0000000015>

A request retrieves a JSON representation of the object, including the relations with references (id and label) to other objects.

Querying

The database is also queryable by the api, under url <https://service.arthurianfiction.org/search>. Queries are specified as a SOLR query (SOLR is the underlying indexing service) of the type `q=[Solr Query]&sort=[Solr sortfield]`, for example `q=cycle_name:Lancelot AND city:Bern&sort=cycle_name`. SOLR queries are made using a HTTP POST request.

The service returns a queryid, that may be used for reference and further processing. The returned result is in the form [https://service.arthurianfiction.org/search/\[QRY000XXXXX\]](https://service.arthurianfiction.org/search/[QRY000XXXXX]) and may be retrieved by specifying further parameters, for example [https://service.arthurianfiction.org/search/\[QRY000XXXXX\]?start=0&rows=200](https://service.arthurianfiction.org/search/[QRY000XXXXX]?start=0&rows=200)

The results may be fetched using a HTTP GET request

Rik Hoekstra, december 2012